

# Confined Space Blowers

## FEATURES

- Polyethylene housing and canister assembly
- Super quiet
- Polypropylene nine-blade fan
- Carry-handle molded into blower
- Steel, powder-coated grill
- Safety-orange
- Lightweight
- Corrosion, UV, and chemical resistant



## CONFINED SPACE BLOWER MODELS AND SPECIFICATIONS

Model No.	HP	Max RPM	Cord	Plug	Free Air Output	Dimensions	Weight
UF-9533	1/3	3400	20' AWG 4.5A-2.2A/115v (60 Hz)	NEMA 5-15P	831 CFM	13.25" x 12" x 13.75" L x W x H	17 lbs.
UF-9533-15 <sup>◇</sup>	1/3	3400	20' AWG 4.5A-2.2A/115v (60 Hz)	NEMA 5-15P	831 CFM	32" X 13.5" X 14.5" L x W x H	33 lbs.
UF-9533-25 <sup>◇</sup>	1/3	3400	20' AWG 4.5A-2.2A/115v (60 Hz)	NEMA 5-15P	831 CFM	32" X 13.5" X 14.5" L x W x H	38 lbs.
UF-9538 <sup>#</sup>	1/3	3250	25' SJOOW 18/3 AWG 300V 2.2A/115v	NEMA 115V, 20 amp, ECP Type	900 CFM	13.25" x 12" x 13.75" L x W x H	20 lbs.
UF-9538-15 <sup>#◇</sup>	1/3	3250	25' SJOOW 18/3 AWG 300V 2.2A/115v	NEMA 115V, 20 amp, ECP Type	900 CFM	34.5" X 13.5" X 14.75" L x W x H	37 lbs.
UF-9538-25 <sup>#◇</sup>	1/3	3250	25' SJOOW 18/3 AWG 300V 2.2A/115v	NEMA 115V, 20 amp, ECP Type	900 CFM	34.5" X 13.5" X 14.75" L x W x H	44 lbs.

<sup>◇</sup> Model includes ducting

<sup>#</sup> Model is explosion proof / intrinsically safe.

## CONFINED SPACE BLOWER DUCTING AND ACCESSORIES

Item No.	Description
UF-9500-06	8" Diameter Ducting, 6 Feet Length
UF-9500-15	8" Diameter Ducting, 15 Feet Length
UF-9500-25	8" Diameter Ducting, 25 Feet Length
UF-9500-15EX	8" Diameter Ducting, 25 Feet Length, Statically Conductive
UF-9500-25EX	8" Diameter Ducting, 25 Feet Length, Statically Conductive
UF-9500-35	8" Diameter Duct Storage Rack
UF-9600-50	Adapter / Reducer, 16" to 8" Diameter
UF-9540	Ground Fault Interrupter
UF-9200-01	8" Duct to Duct Ring Conductor
UF-9510	Saddle-Vent, Manhole Style
UF-9511	Saddle-Vent, Tank Style
UF-9510-01	Universal Mount
UF-9510-90	Elbow For Saddle Vent

## STANDARD CONFINED SPACE BLOWER DUCTING

Standard ducting for blower UF-9533-15 and UF-9533-25 is made of a single-ply, lightweight vinyl/polyester, with a 180° F temperature resistant PVC coating. The ducting features a non-collapsible retractable design with class 1 hard drawn spring steel wire helix. The ducting is yellow with black wear-strips and integrated nylon attachment strap.

## HAZARDOUS LOCATION RATINGS FOR UF-9538 MODEL BLOWERS

Class: I	Class: II
Divisions: 1 & 2	Divisions: 1 & 2
Groups: C & D	Groups: F & G

Hazardous location ducting included with UF-9538-15 and UF-9538-25 is made of black single-ply, lightweight vinyl/polyester, coated with neoprene 250° F, temperature resistant. The ducting is a non-collapsible retractable design with Class 1 hard drawn spring steel wire helix.